

SD/HD/3G-SDI Multi-Format Monitors


LVM-232W-A

Multi Format



제품 규격

- Main Body : 552.5 x 354 x 66.1 (mm) / 21.75 x 13.93 x 2.6 (inch)
- With stand : 599.7 x 381.8 x 142 (mm) / 23.61 x 15.03 x 5.59 (inch)
- Weight : 6.9kg / 15.21lbs



LCD

Size	23"
Resolution	1920 x 1080 (16:9)
Pixel Pitch	0.2652 mm
Color Depth	16.7M
Viewing Angle (Typ.)	178°(H) / 178°(V)
Luminance (Max.)	250 cd/m ² (center)
Contrast Ratio	1000:1
Display Area	509(H) x 286(V)

1920x1080 Full HD 해상도와 광시야각을 가진 23" 모니터

LVM-232W-A는 3G-SDI를 비롯한 다양한 영상 포맷과 강력한 전문가용 기능을 탑재한 다목적의 보급형 모니터입니다. Full HD 해상도의 최신의 IPS 광시야각 LCD 패널을 채용한 이 모니터는 티브이로직의 영상처리 기술과 결합되어 정확한 색상과 우수한 영상품질을 재현합니다.



Product Highlights

- 23" 1920 x 1080 (16:9) Resolution
- 3G-SDI Level A/B
- Audio Level Meter Display
- Blue Only
- Focus Assist
- H/V Delay
- Key lock
- Luma(Y') Zone Check
- Marker
- Mono
- Range Error
- Time Code Display
- UMD
- User Aspect
- Various Scan modes
- Waveform/Vectorscope
- Zoom
- CC-608 ANC
- CC-608 LINE 21
- CC-708
- TVLogic Color Calibration Utility

Input

1 x BNC	Analog Input (Composite)
2 x BNC	3G SDI A/B Channel Input
1 x HDMI	HDMI Input
1 x DVI-I	DVI Input

Output

1 x BNC	Analog Output (Composite)
1 x BNC	3G/HD/SD-SDI OUT

Input Signal

Analog (Composite)	CVBS
3G-SDI	2.970Gbps
HD-SDI	1.485Gbps
SD-SDI	270Mbps
DVI-Analog	640x480/720x400/800x600/1024x768/1280x768/1280x1024/1366x768/1920x1080
DVI-D (PC & HDMI)	640x480/720x400/800x600/1024x768/1280x768/1280x1024/1366x768/1920x1080/1080p(24/25/30/50/60)/1080i(50/60)/720p(50/60)/480i(60)/480p(60)/576i(50)/576p(50)
HDMI (PC & HDMI)	640x480/720x400/800x600/1024x768/1280x768/1280x1024/1366x768/1920x1080/1080p(24/25/30/50/60)/1080i(50/60)/720p(50/60)/480i(60)/480p(60)/576i(50)/576p(50)

Analog Input Spec

CVBS	1.0Vp-p (With Sync) NTSC. PAL
------	-------------------------------

SDI Input Signal Formats

SMPTE-425M-A/B	1080p(60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF) 1080i(60/59.94/50)
SMPTE-274M	1080i(60/59.94/50)/1080p(30/29.97/25/24/24sF/23.98/23.98sF)
SMPTE-296M	720p (60/59.94/50)
SMPTE-260M	1035i (60/59.94)
SMPTE-125M	480i (59.94)
ITU-R BT.656	576i (50)
Audio IN	Embedded Audio / Analog stereo (Phone Jack)
Audio OUT	Analog stereo (Phone Jack) / Internal Speaker (Stereo)
Power	DC 12V / AC 100 ~240V (50~ 60 Hz)
Power Consumption (Approx.)	60Watts
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Accessory	AC Power Cord / Stand

* 제품 사양은 사전 공지 없이 변경될 수 있습니다.

옵션 액세서리

